JCB ENERGY ELECTRIC POWER INDUSTRY

TAT AL

JUENERGY

MADRID / SPAIN





231 / 400 V – 50 Hz & 277 / 480 V – 60 Hz







GENERATOR GENERAL INFORMATION

GENERATOR	FREQUENCY	VOLTAGE	POWER FACTOR	SPEED	DIESEL ENGINE		ALTERNATOR		TYPE OF	GENERATOR OUTPUT		UTPUT		
Model	Hz	V	Cos Q	Rpm	Brand	Model	Series	Brand	Model	Series	Operation	kVA	kW	А
								ž			Standby	720,0	576,0	1.040,5
JDD 720	50	231/400	0.8	1500				C		355M1	Prime	654,5	523,6	945,9
					DOOSAN	DP180LB	DP	Z	JCB		Continuous	458,2	366,5	662,1
					DOOSAN	DI 100LD	DF 180LB DF	PENERG	100	355M	Standby	780,0	624,0	1.127,2
JDD 780	60	277/480	0.8	1800							Prime	709,1	567,3	1.024,7
											Continuous	496,4	397,1	717,3
 Diesel Engines with Advanced Technology and Quality Alternators with Advanced Technology and Quality Low Exhaust Emission Control Panel Suitable for Flexible Application Patented Compact Designed and Sound proof Canopy Low Operating Cost, Suitable for Heavy-Duty Durability, Low Noise Level 					 Fuel Low Globa Wide High 	Filter wit Fuel Cons al Techni Range o Quality a	h Water sumptior cal Servio of Afforda and Relia	and Parti n, Low Oil ce and Ma able Spare ble Techn	cle Separ Consump aintenance Parts ology					

STAND BY POWER RATING – (ESP):

ESP is applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the Stand by Power rating. This rating should be applied where reliable utility power is available. A Stand By rated engine should be sized for a maximum of an 70% average load factor and 200 hours of operation per year. This includes less than 25 hours per year at the Stand by Power rating. Stand By ratings should never be applied except in true emergency power outages. Negotiated power outages contracted with a utility company are not considered an emergency.

PRIME POWER RATING – (PRP):

Applicable for supplying electric power in lieu of commercially purchased power. Prime Power applications must be in the form of one of the following two categories:

UNLIMITED TIME RUNNING PRIME POWER (ULTP):

PRP (Prime Power) is available for an unlimited number of hours per year in a variable load application. Variable load should not exceed a 70% average of the Prime Power rating during any operating period of 250 hours. The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

LIMITED TIME RUNNING PRIME POWER (LTP):

LTP (Limited Time Prime Power) is available for a limited number of hours in a no variable load application. It is intended for use in situations where power outages are contracted, such as in utility power curtailment. Engines may be operated in parallel to the public utility up to 750 hours per year at power levels never to exceed the Prime Power rating. The customer should be aware, however, that the life of any engine will be reduced by this constant high load operation. Any operation

CONTINUOUS POWER RATING (COP):

COP is the power that the engine can continue to use under the prescribed speed and the specified environment condition in the normal maintenance period stipulated in the manufacturing plant. And Continuous Power is applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.



231 / 400 V – 50 Hz & 277 / 480 V – 60 Hz



PAY ATTENTION TO THE POINTS BELOW IN PICKING AND USING THE GENERATOR

* Generators can work on Continuous Power at 70% of Prime power value if only all maintenances are done on time with original spare parts and high-quality oils that manufacturer advice.

* Generators should not operate below 50% of Prime Power value. In such a case, the engine will burn excessive oil and eventually have irreparable damage.

* If your need is 1000 kVA or above, you should prefer Synchronic Systems with 2-3 generators with failure back up and simultaneous aging.

 $\ensuremath{^*}$ These points will provide advantage for you with purchasing and operating the generator.

GENERATOR DIMENSIONS AND TECHNICAL DRAWINGS





VALUES		OPEN TYPE GENERATOR	CANOPY TYPE GENERATOR
WIDTH	mm	1400	1646
LENGTH	mm	3311	4632
HEIGHT	mm	1980	2641
WEIGHT (NET)	Kg	3386	4240
FUEL TANK CAPACITY	L	1066	400

SYMBOL	OPEN	CANOPY
L	3311	4632
W	1400	1646
н	1980	2000
S		641
А	560	
В	1200	
С	1200	
D1		1002
D2		800
D3		800
D4		800
D5		800



FUEL CONSUMPTION

PERCENT OF PRIME POWER	1500 rpm		1800 rpm		
	g/kWh	l/hr	g/kWh	l/hr	
110 %	200,0	144,9	200,0	156,4	
100 %	195,0	128,3	195,0	138,7	
75 %	197,0	97,2	197,0	105,1	
50 %	212,0	69,7	212,0	75,4	



231 / 400 V – 50 Hz & 277 / 480 V – 60 Hz



DIESEL ENGINE MAIN TECHNICAL PARAMETERS

General Engine Data								
Engine Model		DP180LB						
-			4-Cycle, V-Type, 10-Cylinder Diesel, Water Cooled, Turbo Charged & Intercooled					
Engine Type		o-cylinder Diesel, V	water Cooled, Turbo C	larged & intercooled				
Bore x Stroke		128 x 142 mm						
Displacement		18.273 liters						
Compression Ratio		15: 1						
Rotation		Counter clockwise	e viewed from Flyw	heel				
Firing Order		1-6-5-10-2-7-3-8-4	4-9					
Fuel System		Bosch in-line "P" t	type					
Governor		Electronic						
Governor Class		G3						
Cooling System								
Total System Coolant Capacity		21L						
Thermostat Operation Range		80~90°C						
Maximum Temperature to Engine		105°C						
Minimum Temperature to Engine		70°C	70°C					
Coolant Temperature Alarm		105°C	105°C					
Limits of the Environment Temper	rature	52°C	52°C					
Lubrication System								
Lubrication Oil Capacity		34L						
Lubrication Oil Pressure		min 250 kPa (50H	min 250 kPa (50Hz) /min 300 kPa (60Hz)					
Lubrication Oil Temperature		At normal operati	At normal operation 105°C, Maximum 125°C					
Lubrication Oil Consumption as %	Fuel Consumption	0.1 % maximum						
Pressure of Oil Relief Valve Openi	ng	550 ± 50 kPa						
Electrical System								
Alternator		28.5V x 45A alternator						
Starter Motor		24V x 7.0 kW						
Fan								
Diameter		915mm	915mm					
Number Of Blade 7								
Material		Plastic						
	DOOSAN IN	IFRACORE GENSET	ENGINE					
Engine Model	rpm	Gross Engine C		Typical Generat				
0	•	Stand-by	Prime	Stand-by	Prime			
DP180LB	1500	612	556	719	653			
	1800	661	601	777	706			







231 / 400 V – 50 Hz & 277 / 480 V – 60 Hz



JCB ALTERNATOR TECHNICAL PARAMETERS AND SPECIFICATIONS



ALTERNATOR TECHNIC	AL PARAMETERS				
Insulation Class		Н	Field Control System		Self-Excited
Winding Pitch		2/3 - (N° 6)	A.V.R. Model	Standard	SX440
Wires		12	Voltage Regulation	%	± 1
Protection		IP 23	Sustained Short-Circuit Current	10 sec	300% (3 IN)
Altitude	m	1000	Total Harmonic (*) TGH / THC	%	< 4
Overspeed	rpm	2250	Wave Form: NEMA = TIF - (*)		< 50
Air Flow	m³/sec.	1,035	Wave Form: I.E.C. = THF - (*)	%	< 2
Bearing Drive	N/A	-	Bearing Non-Drive	Bearing	6314-2RZ
Rotor Winding	100%	Copper	Stator Winding	100%	Copper

50 HZ / 231-400V COSQ 0,8 / 1500 RPM

STANDARD USING ALT	OPTIONAL USING ALTERNATOR								
BRAND/MODEL	JOENERGY.	JCB 355M1		LEROY-SOMER		TAL0473F	STAMFOR	S5L1D-F	4
DUTY				Continuous				Stand By	
AMBIENT	C°			40°C				27°C	
CLASS / TEMP. RISE	C°			H/ 125° K				H/ 163° K	
SERIES STAR	V	380/220	400/231	415/240	1 Phase	380/220	400/231	415/240	1 Phase
PARALLEL STAR	V	190/110	200/115	208/120	220	190/110	200/115	208/120	220
SERIES DELTA	V	220	230	240	230	220	230	240	230
OUTPUT POWER	kVA	659,0	659,0	684,0	-	725,0	725,0	752,0	-
OUTPUT POWER	kW	527,2	527,2	547,2	-	580,0	580,0	601,6	-

60 HZ / 277-480V COSQ 0,8 / 1800 RPM

STANDARD USING ALTERNATOR				OPTIONAL USING ALTERNATOR					
BRAND/MODEL	JOENERGY	JCB 355M		LEROY-SOMER		TAL0473E	STAN	FORD	S5L1D-E4
DUTY				Continuous				Stand	Ву
AMBIENT	C°		40°C			27°C			
CLASS / TEMP. RISE	C°			H / 125° K				H/163	З° К
SERIES STAR	V	416/240	440/254	480/277	1 Phase	416/240	440/254	480/27	77 1 Phase
PARALLEL STAR	V	208/120	220/127	240/138	-	208/120	220/127	240/13	38 -
SERIES DELTA	V	240	254	277	240	240	254	277	240
OUTPUT POWER	kVA	720,0	720,0	747,6	-	792,0	792,0	822,0) -
OUTPUT POWER	kW	576,0	576,0	598,1	-	633,6	633,6	657,6	; -





231 / 400 V – 50 Hz & 277 / 480 V – 60 Hz



CONTROL MODULE ALERTS

Emergency Stop Malfunction High Generator Frequency Low Generator frequency, Low Load Over Current, Unbalanced Current Low Generator Voltage High generator Frequency Phase sequence error Overload, Heat Sensor Broken Low Water Level (Optional) Low Oil Pressure, Reverse Power Low Water Temperature Start Error, Stop Error Magnetic Pickup Error Charge Alternator Error Unbalanced Load Maintenance Time Alarm Low Speed, High Speed Broken Oil Sensor Cable High Oil Temperature (Optional) Low Fuel Level (Optional), High Battery Voltage Low Battery Voltage, High Water Temperature Electronic Can bus Errors (ECU)

CONTROL PANEL SPECIFICATIONS



- Powder Painted Steel Panel with
- Lockable Door
- ATS (Automatic Transfer Panel) Optional
- Control Module
- Battery Charger
- Emergency Stop Button

- Terminal Blocks
- Load Output Terminal
- System Protection MSBs
- Circuit Breaker-Optional
- LCD Screen
- Control Relays
- Backlit, 128x64 Pixels

CONTROL MODULE TECHNICAL PARAMETERS

Brand		Brand	Trans-MIDIAMF.232.GP
Dimensions	120mmx94mm.	Protection Class	IP65 From the Front
Weight	260 gr.	Environmental Conditions	2000 meters above sea level
Ambient Humidity	Max. %90.	Ambient Temperature	-20°C to +70°C
DC Battery Supply Voltage	8 - 32 V	Battery Voltage Measurement	8 – 32 V
Network Frequency	5 - 99,9 Hz	Mains Voltage Measurement	3 - 300 V phase -Neutral, 5 - 99,9 Hz
Generator Voltage Measurement	3 - 300 V	Generator Frequency	5 - 99,9 Hz
Current Transformer Secondary	5A	Working Period	Continuous
Charge Alternator Voltage Measurement	8 - 32 V	Charge Alternator Excitation	210mA &12V, 105mA &24V Nominal 2.5W
Communication Interface	RS-232	Analog Sender Measurement	0 - 1300ohm
Generator Contactor Relay Output	5A & 250V	Mains Contactor Relay Output	5A & 250V
Solenoid Transistor Outputs	1A with DC Supply	Start Transistor Outputs	1A with DC Supply
Configurable-3 Transistor Outputs	1A with DC Supply	Configurable-4 Transistor Outputs	1A with DC Supply



231 / 400 V – 50 Hz & 277 / 480 V – 60 Hz



CONTROL MODULE FUNCTION

Mains Voltage Level Control	Generator Voltage Level Control	3 Phase Generator Protections	3 Phase AMF Function	Alarm Horn
Network Frequency Level Control	Generator Frequency level Control	- High / Low Voltage	- High / Low Frequency	Heater Tube Thermostat Control
Engine Operating Option Control	Generator Current Level Control	- High / Low Frequency	- High / Low Voltage	Modbus and SNMP
Engine Stop Option Control	Generator Powder Level Control	 Current / Voltage Asymmetry 	- High / Low Water Temperature	Working Hour
Engine Speed (RPM) Level Control	Generator work Schedule and Timing Control	- Overcurrent / Overload	- High / Low Load	Ground Leakage
Battery Voltage Options Times	Oil Pressure Controllers Control	Overheat Control	Mains., Generator ATS Control	Analog Modem
Check Engine Maintenance Times	Configurable Analog Inputs and Outputs	1 Phase or 3 Phase, Phase Selection	Network, Voltage, Frequency Display	Ethernet, USB, RS232, RS485
Communication Interfaces GPRS, GSM	Keeping Error Records of Past Events	Parameter Setting via Control Module	Parameter Setting via Computer	Selectable Protection Alarm / Shutdown
Engine Speed, Voltage, Earning	Configurable Programmable Digital Inputs and Outputs	Water Temperature Current and Frequency	Hours of Operation Phase sequence	Battery Voltage Oil Pressure

SOUND PROOF CANOPY AND BASE FRAME (CHASIS) SPECIFICATIONS




- Special, Registered JCB Energy Design and Colour
- A1 Quality DKP / HRU / Galvanized Steel
- Sensitive Twist on Automatic Press Brake
- Delicate Cut on Automatic Punch and Laser Bench
- Sensitive Welding on Robotic Welding Bench
- Chemical Cleaning Nano Technology Before Painting
- Robotic Painting with Electrostatic Powder Paint
- Drying and stabilizing on 200 °C Ovens
- 1500 Hour Salt Test
- Glass wool Isolation, A1 Class Material -50/+500 ºC
- Special Covering Over Glass Wool
- Best Sound Level (in Dba)
- Temperature Tests
- Rustproof Accessories


- Cable Exit Connectors and Glands
- Emergency Stop Button
- Fuel Level Gauge
- Fuel Drain Cap
- Fuel Inlet and Return Records
- I permeability Test for Fuel Tank
- Vacuumed Rubber Mounted
- High Quality weatherstrips
- High Quality Shock Absorbers
- Fuel Filling Cap (with ventilation)
- Lifting and Carrying Equipment
- Internal Exhaust Mufflers (Silencers)
- External Exhaust Mufflers (Silencers)
- Radiator water Filling Cap
- Daily Fuel Tank, External Fuel Tank

OUR CERTIFICATES











CERTIFICATE HEALTHY & SAFE WORKPLACE CERTIFICATE

JUENERGY JCB ENERGY ELECTRIC POWER INDUSTRY

CALLE, DE: TRESPADERNE, NUM 7 PLANTA 3, PURKTAC 2004 MANDINE - OKCHELD, NEMM ETal: been emphasize of balances, which the physical angularement for DDMD ID measure, which the physical after hit for sciolar of the Meddy and Safe Weighteen Cart

with in the score of the Healthy and Safe Workplane Cardinate program, PACTORIES - PRODUCTION LOCATIONS: ELECTRICAL AND ELECTRONICS INDUSTRY

to by fallfing the of the bosinesi


Compliant Anaster 1 CCRF ERT-11.2023.3650 Compliant Annual Nation 107.11.2023 Compliant Fability 206.11.2025


Complicate Fadulty : 04.11.2025






CE -verta-106188 -verta-106189











DNV

MANAGEMENT SYSTEM CERTIFICATE

Certificate no: Initial certification date: D012084 14 August 2007

The site contribute the management system of **HD Hyundai Infracore Co., Ltd. Head Office & Incheon Plant** 40 (hipping) - Drops, Inderko, 2202, Republic of Korea and the sites an mentioned in the appendix accompanying this cartificate has been toxed to conform to the Environmental Management System standard. 150 (1400):1201

Valid: 14 October 2023 - 13 October 2026

The certificate is walls for the following scope: Design, Development, Manufacture, Servicing of Internal Combustion Engine for use in Marine Industry, General Industry and Automotive Industry, and Earth Moving Equipment[Excavator, Wheel Loader, Dezer], Testing of Earth Moving Equipment[Excavator and Wheel Loader].





DNV

<section-header><section-header><text><text><text><text><text><text><text><text>





Lanuari de meterre metorerres de Madera SALIDA IF de Registra 1415/80.645 Focies 2597.2223 12/82.09

RENE SANCHEZ ROMAN, MANAGER CH'THE DEMARTMENT O' LIGAL ADMSONY SERVICES AND THE DATAINGE OF THE OFFICIAL OMAXBER OF COMMERCE, MOUERRE AND SERVICES OF MARIND, WITH INDUSTRIED OFFICE AT PLAZA DE LA INDERDIDICA 1, MARIND, DAVIN

CERTIFY. That, according to the background data on moord at this Chambar and others produced by the Company

CB-BERGY RECEISE FOMBLINGOTINE SL, a Company with Tax ID. Namine H1997554, and to registress office a strengt impactements in 2000 Masking is registred on MMp 2004, and the heading of the 3D Service comparise, of the Economic Activities Tax Tarihi function 540 spectrum the future gradient of the Service comparison.

· Menufacture of electrical material for use and equipment

In whites whereast, for the appropriate purpose, i have issued and signed this Certificate, to which Latts the stamp of this Chamilee, in Madrial on 28 July 2004.





Libration and Annual Annua

BENE SANCHEZ ROMAN, DIRECTORA DEL DERVICTAMENTO DE ASESORIA IMPRICA Y CINSO DE LA CIMARIA OFICIAL DE COMERCIO, INDUSTINA Y SURVICIS DE MARIRO, CON OCIACIONO SOCIAL EN LA TILAZA DE LA INDEPENDENCIA M. L'ANDRO-ENTANA CERTIFICA Qua de los antecedentes que obrin en ente Cuipenación y de coso entididos por la recordad, muntar

HIMPING due la compañía ACI INTROV ELECTIC ENVERT ADALTINE 4.1. a con accéption preventi de proclamation equation, constituit de moltante existence hanne acception preventi de la constituit de moltante existence hanne Calegoria de Marcía de Calegoria e Calegoria e la territoria de la constituit de la constituit de moltante antibula y de la Statutaria de la constituit de la constituit de antibula y de la Statutaria de la constituit de la constituit de antibula y de la Statutaria de la constituit de la constituit de antibula y de la Statutaria de la compañía (CE MENION ELECTINE CROME MOLISTIN SL), constituit que la las policitas Statutaria.

"Activided propipal 27.11 Astronomy de matures, geberadores y transformador eléctricos".

METRODA: METRODA: An explore of expensive due la socitura de contitución, el capital encil de la compañía (x.p. 1980/07 18/2702). EXAME INDUSTRY SLL se fija en la centidad de 1980/08 el (Electorizador Met HONCENTOX MITEL Electorizador del participacione) sociales, de 1000 (UNI EIRO) de valor nominal cada una, minerador complementente al 1.a 19302 ambis: induzióne, que son integramente ausuridas y desemblostar por de com fundador.

Operational processing to consider the electronic de construction shadow en plandow anthrefore la companie XB INERSY IEEE/INER FORME NOUTRY SL, que por al islama de Administrator (Longo normas par lange) informational and an encontre y impresentation en in marcianti (Longo constructional and administrational and the interpretation in an encontre (Longo constructional and administrational and the interpretation enconstruction (Longo Constructional and administrational and the interpretational administration (Constructional and administrational administrational administrational administrational administrational administrational administrational administrational administration (Constructional administrational administration administration administrational admininterventerventerventerventerve

Organ productions of a compariso ACI MINITARY FILETING: CONVERT INFULSTING C., con domicilia an calle Tospodeme dament 7, 20042. Majolar y provide de Namero de Nerrificación radia 19:207528, conzo dad de este en el gruportyperjone. Mad de la Soción II emprenensi de las Tartas del Inpostos sobre Actividades Económicas, que fanda para ejecto ha activada Térmicani en en entratio del Minister de Namero de Namero de Ventoria de Soción II de Soción II de esperaneira de las Tartas del Inpostos sobre Actividades Económicas, que fanda para escon ha activada Térmicanis en antenida (dérina de Utalizentos) y reglamenteri.









R

www.jcbenergy.com



9

Π