JCB ENERGY ELECTRIC POWER INDUSTRY

JUENERGY

-VERTA-106188 -VERTA-106189

MADRID / SPAIN



www.jcbenergy.com



JVP 94

231 / 400 V – 50 Hz





GENERATOR GENERAL INFORMATION

GENERATOR	FREQUENCY	VOLTAGE	POWER FACTOR	SPEED	DIESEL EI	NGINE	ALTERN	IATOR		TYPE OF	GENER		
			PACIOR										
Model	Hz	V	Cos Q	Rpm	Brand	Model	Brand	Model	Series	Operation	kVA	kW	A
							, di			Standby	94,0	75,2	135,8
JVP 94	50	231/400	0.8	1500	Volvo Penta	TAD530GE	O ENERGY	JCB	225M2	Prime	85,5	68,4	123,5
					renta					Continuous	59,8	47,9	86,4
 Diesel Engir 	nes with Advar	nced Techno	logy and Quali	ty		 Tropical 50) °C Radia	ator, First	Class Pro	duct Support			
 Alternators 	with Advance	d Technolog	y and Quality			 Fuel Filter with Water and Particle Separator 							
Low Exhaus	t Emission					 Low Fuel Consumption, Low Oil Consumption 							
 Control Par 	 Control Panel Suitable for Flexible Application 					 Global Technical Service and Maintenance Support 							
 Patented Compact Designed and Sound proof Canopy 				 Wide Range of Affordable Spare Parts 									
 Low Operating Cost, Suitable for Heavy-Duty 				 High Quality and Reliable Technology 									
 Durability, Low Noise Level 				 Half Century Experience in Generator Manufacturing 									

STAND BY POWER RATING – (ESP):

ESP is applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the Stand by Power rating. This rating should be applied where reliable utility power is available. A Stand By rated engine should be sized for a maximum of an 70% average load factor and 200 hours of operation per year. This includes less than 25 hours per year at the Stand by Power rating. Stand By ratings should never be applied except in true emergency power outages. Negotiated power outages contracted with a utility company are not considered an emergency.

PRIME POWER RATING - (PRP):

Applicable for supplying electric power in lieu of commercially purchased power. Prime Power applications must be in the form of one of the following two categories:

UNLIMITED TIME RUNNING PRIME POWER (ULTP):

PRP (Prime Power) is available for an unlimited number of hours per year in a variable load application. Variable load should not exceed a 70% average of the Prime Power rating during any operating period of 250 hours. The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

LIMITED TIME RUNNING PRIME POWER (LTP):

LTP (Limited Time Prime Power) is available for a limited number of hours in a no variable load application. It is intended for use in situations where power outages are contracted, such as in utility power curtailment. Engines may be operated in parallel to the public utility up to 750 hours per year at power levels never to exceed the Prime Power rating. The customer should be aware, however, that the life of any engine will be reduced by this constant high load operation. Any operation

CONTINUOUS POWER RATING (COP):

COP is the power that the engine can continue to use under the prescribed speed and the specified environment condition in the normal maintenance period stipulated in the manufacturing plant. And Continuous Power is applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.







PAY ATTENTION TO THE POINTS BELOW IN PICKING AND USING THE GENERATOR

231 / 400 V - 50 Hz

* Generators can work on Continuous Power at 70% of Prime power value if only all maintenances are done on time with original spare parts and high-quality oils that manufacturer advice.

* Generators should not operate below 50% of Prime Power value. In such a case, the engine will burn excessive oil and eventually have irreparable damage.

* If your need is 1000 kVA or above, you should prefer Synchronic Systems with 2-3 generators with failure back up and simultaneous aging.

 $\ensuremath{^*}$ These points will provide advantage for you with purchasing and operating the generator.


GENERATOR DIMENSIONS AND TECHNICAL DRAWINGS





VALUES		OPEN TYPE GENERATOR	CANOPY TYPE GENERATOR	
WIDTH mm		800	1000	
LENGTH	mm	2036	2600	
HEIGHT	mm	1677	1510	
WEIGHT (NET)	Kg	1020	1247	
FUEL TANK CAPACITY		190	205	

SYMBOL	OPEN	CANOPY
L	2036	2600
W	800	1000
н	1677	1510
S	132	150
Α	625	
В	454	
С	536	
D1		750
D2		750
D3		520
D4		
D5		



PERCENT OF PRIME POWER	FUEL CONSUMPTION		
	l/hr		
110 %	21,4		
100 %	19,0		
75 %	14,4		
50 %	10,1		





JVP 94 231 / 400 V – 50 Hz



DIESEL ENGINE MAIN TECHNICAL PARAMETERS

GENERAL		
Number of Cylinders		4
Configuration		Vertical, in line
Aspiration		Turbo Charged
Combustion System		Direct injection
Compression Ratio		18:1
Bore	mm	108
Stroke	mm	130
Displacement	L	4,76
Governing Type	-	Mechanic
Governing Class		G2
Rotation		Counterclockwise
Firing Order		1-3-4-2
Emission		EU Stage 2
FILTERS		
Air Filter		Dry Type, Replaceable
Fuel Filter		Element type, Replaceable
Oil Filter		Element Type, Particulate Trap
ELECTRICAL SYSTEM		
Voltage	V	12
Starter	kW	3,1
Alternator Output Ampers	A	55
Alternator Output Voltage	V	14
Batteries Capacity	Ah	85
FAN	All	
Diameter	mm	516
Drive Ratio		1.73:1
Number of Blades		7
Material		Metal
Type		Blowing
COOLING SYSTEM		Blowing
Radiator Type	50ºC	Tropical
Total Coolant Capacity	L	19,7
Max. Perm. Coolant Outlet Temperature	°C	105
Max. Perm. Flow Resist. (Cool. System And Piping)	bar	0,1
Max. Temperature of Coolant Warning	°C	95
Max. Temperature of Coolant Shutdown	°C	98
Thermostat Operation Temperature - Initial Open	°C	83
	°C	95
Thermostat Operation Temperature - Full Open Delivery of Coolant Pump	≞C m ³/ h	2,71
Min. Pressure Before Coolant Pump	bar	0,3
Radiator Face Area	m ²	0,3
Rows	Row	2
	Per / Inch	12
Matrix Density Material		Aluminum
Width of Matrix	mm	454
	mm	636
Height of Matrix	mm kBa	
Pressure Cap Setting	kPa kPa	90
Estimated Cooling Air Flow Reserve	kPa	0,125
Engine Pre Heater-Tube (with Circulation Pump)	W	1500





DIESEL ENGINE MAIN TECHNICAL PARAMETERS

LUBRICATION SYSTEM		
Total System	L	13
Minimum Oil Level	L	9
Nominal Motor Operating Temperature	ōC	49
Lubricating Oil Pressure (Rated Speed)	bar	4,8
Relief Valve Opens	kPa	300
Oil / Fuel Consumption Ratio	%	0,08
Normal Oil Temperature	ōC	110

DIESEL ENGINE MATCHING PARAMETERS - 50 HZ

50 HZ @ 1500 R/MIN		STAND BY
Gross Engine Power	kW	89,0
Net Engine Power	kW	83,0
Fan Power Consumption (Belt Pulley Driven)	kW	5,9
Other Power Loss	kW	-
Mean Effective Pressure	MPa	1500,00
Intake Air Flow	m ³ /min	5,54
Exhaust Temperature Limit	°C	540
Exhaust Flow	m ³/ min	16,30
Boost Pressure Ratio		9,00
Mean Piston Speed	m / s	6,5
Cooling Fan Air Flow	m ³/ min	72,0
Typical Generator Output Power	kVA	93
HEAT REJECTION		STAND BY
Energy in Fuel (Heat of Combustion)	kW	231,0
Gross Heat to Power	kW	89,0
Energy to Coolant and Lubricating Oil	kW	48,0
Energy to Exhaust	kW	75,0
Heat to Radiation	kW	9,0



JVP 94

231 / 400 V – 50 Hz



ALTERNATOR SPECIFICATIONS



ALTERNATOR TECHNICA	L PARAMETERS				
Insulation Class		Н	Field Control System		Self-Excited
Winding Pitch		2/3 - (N° 6)	A.V.R. Model	Standard	SX460
Wires		12	Voltage Regulation	%	± 1
Protection		IP 23	Sustained Short-Circuit Current	10 sec	300% (3 IN)
Altitude	m	1000	Total Harmonic (*) TGH / THC	%	< 5
Overspeed	rpm	2250	Wave Form: NEMA = TIF - (*)		< 50
Air Flow	m³/sec.	0.216	Wave Form: I.E.C. = THF - (*)	%	< 2
Bearing Drive	N/A	-	Bearing Non-Drive	Bearing	6309-2RZ
Rotor Winding	100%	Copper	Stator Winding	100%	Copper

ALTERNATOR SPECIFICATIONS

50 HZ / 231-400V COSQ 0,8 / 1500 RPM STANDARD USING ALTERNATOR **OPTIONAL USING ALTERNATOR JOENERGY** JCB 225M2 **BRAND/MODEL** TAL044C UC274C LEROY-SOMER **STAMFORD** DUTY Continuous Stand By AMBIENT C° 40°C 27°C **CLASS / TEMP. RISE** C° H/ 163° K H/ 125° K 400/231 1 Phase 1 Phase **SERIES STAR** ۷ 380/220 415/240 380/220 400/231 415/240 PARALLEL STAR ۷ 190/110 200/115 208/120 220 190/110 200/115 208/120 220 SERIES DELTA v 220 230 240 230 220 230 240 230 **OUTPUT POWER** kVA 91,0 91,0 94,0 100,0 100,0 103,0 -_ **OUTPUT POWER** kW 73,0 75,0 80,0 80,0 82,0 73,0 -



JVP 94

231 / 400 V – 50 Hz



CONTROL MODULE ALERTS

Emergency Stop Malfunction High Generator Frequency Low Generator frequency, Low Load Over Current, Unbalanced Current Low Generator Voltage High generator Frequency Phase sequence error Overload, Heat Sensor Broken Low Water Level (Optional) Low Oil Pressure, Reverse Power Low Water Temperature

Start Error, Stop Error Magnetic Pickup Error Charge Alternator Error Unbalanced Load Maintenance Time Alarm Low Speed, High Speed Broken Oil Sensor Cable High Oil Temperature (Optional) Low Fuel Level (Optional), High Battery Voltage Low Battery Voltage, High Water Temperature Electronic Can bus Errors (ECU)

CONTROL PANEL SPECIFICATIONS







- Powder Painted Steel Panel wir Lockable Door
- ATS (Automatic Transfer Panel)-Optional
- Control Module
- Battery Charger
- Emergency Stop Button

- Terminal Blocks
- Load Output Terminal
- System Protection MSBs
- Circuit Breaker-Optional
- o LCD Screen
- o Control Relay
- Backlit, 128x64 Pixels

CONTROL MODULE TECHNICAL PARAMETERS

Brand		Brand	Trans-MIDIAMF.232.GP
Dimensions	120mmx94mm.	Protection Class	IP65 From the Front
Weight	260 gr.	Environmental Conditions	2000 meters above sea level
Ambient Humidity	Max. %90.	Ambient Temperature	-20°C to +70°C
DC Battery Supply Voltage	8 - 32 V	Battery Voltage Measurement	8 – 32 V
Network Frequency	5 - 99,9 Hz	Mains Voltage Measurement	3 - 300 V phase -Neutral, 5 - 99,9 Hz
Generator Voltage Measurement	3 - 300 V	Generator Frequency	5 - 99,9 Hz
Current Transformer Secondary	5A	Working Period	Continuous
Charge Alternator Voltage Measurement	8 - 32 V	Charge Alternator Excitation	210mA &12V, 105mA &24V Nominal 2.5W
Communication Interface	RS-232	Analog Sender Measurement	0 - 1300ohm
Generator Contactor Relay Output	5A & 250V	Mains Contactor Relay Output	5A & 250V
Solenoid Transistor Outputs	1A with DC Supply	Start Transistor Outputs	1A with DC Supply
Configurable-3 Transistor Outputs	1A with DC Supply	Configurable-4 Transistor Outputs	1A with DC Supply



JVP 94 231 / 400 V – 50 Hz



CONTROL MODULE FUNCTION

Mains Voltage Level Control	Generator Voltage Level Control	3 Phase Generator Protections	3 Phase AMF Function	Alarm Horn
Network Frequency Level Control	Generator Frequency level Control	- High / Low Voltage	- High / Low Frequency	Heater Tube Thermostat Control
Engine Operating Option Control	Generator Current Level Control	- High / Low Frequency	- High / Low Voltage	Modbus and SNMP
Engine Stop Option Control	Generator Powder Level Control	 Current / Voltage Asymmetry 	- High / Low Water Temperature	Working Hour
Engine Speed (RPM) Level Control	Generator work Schedule and Timing Control	- Overcurrent / Overload	- High / Low Load	Ground Leakage
Battery Voltage Options Times	Oil Pressure Controllers Control	Overheat Control	Mains., Generator ATS Control	Analog Modem
Check Engine Maintenance Times	Configurable Analog Inputs and Outputs	1 Phase or 3 Phase, Phase Selection	Network, Voltage, Frequency Display	Ethernet, USB, RS232, RS485
Communication Interfaces GPRS, GSM	Keeping Error Records of Past Events	Parameter Setting via Control Module	Parameter Setting via Computer	Selectable Protection Alarm / Shutdown
Engine Speed, Voltage, Earning	Configurable Programmable Digital Inputs and Outputs	Water Temperature Current and Frequency	Hours of Operation Phase sequence	Battery Voltage Oil Pressure

SOUND PROOF CANOPY AND BASE FRAME (CHASIS) SPECIFICATIONS





- Special, Registered JCB Energy Design and Colour
- A1 Quality DKP / HRU / Galvanized Steel
- Sensitive Twist on Automatic Press Brake
- Delicate Cut on Automatic Punch and Laser Bench
- Sensitive Welding on Robotic Welding Bench
- Chemical Cleaning Nano Technology Before Painting
- Robotic Painting with Electrostatic Powder Paint
- Drying and stabilizing on 200 °C Ovens
- 1500 Hour Salt Test
- Glass wool Isolation, A1 Class Material -50/+500 ℃
- Special Covering Over Glass Wool
- Best Sound Level (in Dba)
- Temperature Tests
- Rustproof Accessories


- Cable Exit Connectors and Glands
- Emergency Stop Button
- Fuel Level Gauge
- Fuel Drain Cap
- Fuel Inlet and Return Records
- I permeability Test for Fuel Tank
- Vacuumed Rubber Mounted
- High Quality weatherstrips
- High Quality Shock Absorbers
- Fuel Filling Cap (with ventilation)
- Lifting and Carrying Equipment
- o Internal Exhaust Mufflers (Silencers)
- External Exhaust Mufflers (Silencers)
- Radiator water Filling Cap
- Daily Fuel Tank, External Fuel Tank

OUR CERTIFICATES











CERTIFICATE HEALTHY & SAFE WORKPLACE CERTIFICATE

JUENERGY JCB ENERGY ELECTRIC POWER INDUSTRY

CALLE, DE TRENPADERNE, NUM 7 PLANTA 2, PURITA C 20942 MADRID - (MADRID), NPAIN ETREMON CONTROL TO DRAME & ManBY, and Tafe Worksham

 Kital been retrief to belies a heading well kit Wortsplane Devilicious for officing the essenancement for CDUD 31 measures which the approximation official to be with in the score of the Hadding well Sufe Worksplane Devilicies (angree) FACTORIES - PRODUCTION LOC ATOMNS; ELEXCERIAC AND ELEXTENSINCE INDUSTRY


Conference Analise: 1 CCRCERT-11.2023.3650 Conference Analise: 107.12.2023 Conference Analise: 106.11.2023


Complement Facility : 06.11.2025







CE -VERTA-106188 -VERTA-106189











DNV

MANAGEMENT SYSTEM CERTIFICATE

Certificate no: Initial certification date: D012084 14 August 2007

The site contribute the management system of **HD Hyundai Infracore Co., Ltd. Head Office & Incheon Plant** 40 (hipping) - Drops, Inderko, 2202, Republic of Korea and the sites an mentioned in the appendix accompanying this cartificate has been toxed to conform to the Environmental Management System standard. 150 (1400):1201

Valid: 14 October 2023 - 13 October 2026

The certificate is walls for the following scope: Design, Development, Manufacture, Servicing of Internal Combustion Engine for use in Marine Industry, General Industry and Automotive Industry, and Earth Moving Equipment[Excavator, Wheel Loader, Dezer], Testing of Earth Moving Equipment[Excavator and Wheel Loader].





DNV

<section-header><section-header><text><text><text><text><text><text><text><text>





Lanuari de meterre metorerres de Madera SALIDA IF de Registra 1415/80.645 Focies 2997.2223 12/82/09

RENE SANCHEZ ROMAN, MANAGER CH'THE DERIMETATION OF LIGAL ADVISORY SERVICES AND THE DATAMASE OF THE OFFICIAL OMAXBER OF COMMERCE, MOLERIF AND SERVICES OF MARIND, WITH INDUSTRIED OFFICE AT PLAZA DE LA INDERDIDICA 1, MARIND, DAVIN

CERTIFY. That, according to the background data on moord at this Chambar and others produced by the Company.

CB-BERGY RECEISE FOMBLINGOTINE SL, a Company with Tax ID. Namine H1997554, and to registress office a strengt impactements in 2000 Masking is registred on MMp 2004, and the heading of the 3D Service comparise, of the Economic Activities Tax Tarihi function 540 spectrum the future gradient of the Service comparison.

· Menufacture of electrical material for use and equipment

In whites whereast, for the appropriate purpose, i have issued and signed this Certificate, to which Latts the stamp of this Chamilee, in Madrial on 28 July 2004.





Constant of Analysis Aligna Wide Register 152 (Bi 660 Fecha 3607/3224 tild734

BENE SANCHEZ ROMAN, DIRECTORA DEL DEIWOTMENTO DE ASESORIA IMPORTA Y CINSO DE LA CIMARIA OFICIAL DE COMERCIO, INDUSTINA Y SURVICIS DE MARIRO, CON OCIACIONI SOCIAL EN LA TILAZA DE LA INDEPENDENCIA Y IL IMPORTO-ENTRATA CERTIFICA Que de los antecedentes que obrin en ente Cuipenación y de coso entididos por la recordad, manta

HIMPING due la compañía ACI INTROV ELECTIC ENVERT ADALTINE 4.1. a con accéption preventi de proclamation equation, constituit de moltante existence hanne acception preventi de la constituit de moltante existence hanne Calegoria de Marcía de activitativa en la constituit de moltante hanne acception de la constituit de la constituit de moltante la constituit de activitati à la constituit de la constituit de la constituit de activitati à la constituit de la constituit de la constituit de activitati à la constituit de la constituit de la constituit de activitati à la constituit de la constituit de la constituit de activitati à la constituit de la constituit de activitati à la constituit de la constituit de activitati de

"Activided propipal 27.11 Astronomy de matures, geberadores y transformador eléctricos".

METRODA: METRODA: Can explore and expensive due la socitura die contribución el capital encid de la compartía (x.p. 1948/07 18/2758). ENARE INDUSTRY SLL se fije en la centided de 1940/014 el (Electorization el capital de la contracta d

Organ productions of the comparison of the state of th









R

www.jcbenergy.com



9

Π