

JCB ENERGY ELECTRIC POWER INDUSTRY

MADRID / SPAIN



- Easy handling and operating
- Easy spare parts and maintenance availability
- Security & Protection: For personal safety, necessary protection provisions
- Low oil level protection



Engine

Max. Output Current	(based on the models)	Between 5Hp-10Hp
Speed	RPM	3600
Starting	(12VDC)	Recoil and Electrical
Fuel Consumption	(g/kWh)	Between 280-283
Engine Side Mounted Fuel Tank Capacity	(liters)(based on the models)	Between 2.5- 5.5
Countinuous Operating	(hours)	2.5 – 2.6
Oil Capacity	(liters)	Between 0.8 – 1.65
Noise level: Environmetly low noise level	(dBA@7m)	75

Air Cooled, 4- cycle diesel engine
(178 FP, 170 FP/FEB, 186 FAB/FAEP)

Type

Pump

Inlet – Outlet diameter	(mm-inc)	Between 40-1.5" – 100-4"
Max. Lift Head	(m/ft)	Between 13-42
Suction Debt Head	(m)	8
Max. Pumping Capacity	(lt/min)	Between 167-670
Self Priming Time	(4m /sec.)	Between 40-180

Others

Easy transportable capability		
Dry weight (kg)		Between 38 – 68

PUMP

Inlet-Outlet diameter	(mm/inc)	80-3"
Total Head	(mms)	13
Suction Head	(m)	8
Max. Pumping Capacity	(liter/min)	500
Self-Priming Time	(4 mt/sec.)	120

ENGINE

Model		178FP/FEB
Type		Air Cooled – 4 Stroke Direct Injection- Single Cylinder
Displacement	cm ³	296
Max. Power Output	Hp – 3600 rpm	7
Fuel Tank Capacity	lt	3.5
Fuel Consumption	gr/Kw-H	283
Starting System		FP : Recoil/FEP : Electric Start
Continuous Operating Hours	Hr	2.5
Oil Capacity	lt	1.1
Oil Alert		✓
Noise Level	dBA @7mt	75
Dimensions	LxWxH	560x450x515
Dry Weight	kg	45



www.jcbenergy.es